

POWER, SIMPLICITY AND EFFICIENCY.

Thanks to the E 3000 G series of isodiametric four-wheel drive tractors, ARBOS provides an efficient answer to operators who need an easily handled, agile and stable machine for work on slopes and where there's not much space for manoeuvring. The E 3000 G series includes tractors with power ratings that range from 25 to 38 hp produced in with steering (SW) wheels and the articulated (AR) version, suitable when an even tighter turning radius is required.



THE "ENTRY LEVEL" TRACTOR

+ STEERING AND ARTICULATED

LOWERED, SPACIOUS AND ERGONOMIC COCKPIT



				E		
		3030 G sw	3040 G sw	3045 G sw	3045 G AR	
Туре			Die	esel		
Power rating	kW(hp)	19 (25)	25 (33)	28	3 (38)	
Nominal rate	rpm		28			
N° Cylinders	n°	2 natural aspiration		3 aspirated		
Cooling		Air		Water		
Swept volume	сс	1248	1649			
Tank capacity	It		4		30	
N° Speeds			9 speeds: 6 forv	vard + 3 reverse		
Main clutch			6" diamete			
Front differential lock			Mechanical system, with manual lo			
lear differential lock		Mechanical syst	echanical system, with manual locking through independent levers Mechanical system, with manual locking through pedal			
Speed	Kph	30				
Type of brakes		Rear brakes, drum t	type. Mechanical control. Independe	nt or simultaneous braking and into	egral on the 4 wheels	
Type of steering			Hydraulic, hyd		<u>-</u>	
Steering angle	ng angle		45° 30°			
Туре		Independent at 540 rpm and synchronized with all gears	Independent at	540/750 rpm and synchronized wit	h gearbox speeds	
Clutch			Dry dis	sc type		
Control			Mech	anical		
Гуре			Floating Up ar	nd Down Lifter		
Lifting capacity	Kg	10	00	1	200	
3 point hitch			Class 1		Class 1 and 1N	
Pump flow rate	lt/min	18,5		25		
Rear hydraulic control valves	ear hydraulic control valves		Max 1, double acting			
Safety frame		Folding roll bar				
nstruments		Analog Digital				
Driver's seat		<u> </u>	ı both in horizontal and vertical positic		ed suspension	
Tow hook		·	Cla			
THE RESERVE OF THE PARTY OF THE		SW	SW	SW	AR	
Length	mm	2870	3005	3005	2660	
Width min. and max.	mm	1103 - 1203	1103 - 1203	1110 - 1431	1000 - 1290	
Height to safety frame	mm	1970	1970	2000	2005	
Wheelbase	mm	1155	1155	1155	1294	
Front track min. and max.	mm	896 - 996	896 - 996	1010 - 1200	742 - 1288	
Rear track min. and max.	mm	896 - 996	896 - 996	1010 - 1200	742 - 1288	
Weight with safety frame	Kg	1100	1100	1350	1300	
			4.4"			
Front - Rear (Standard)		7,50 29x12,50"Garden	x16" 29x12,50"Garden - 260/70-16"	8,25x16" -	8,25x16"	



^{*} Tyres considered 7.50x16" (E 3000 G 30 SW - 40 SW) and 8.25x16" (E 3000 G 45 SW - 45 AR)